

HOURS OF SERVICE TELEGRAPH OFFICES

Station	Weekdays	Sat. & Sun.
Greensboro	Continuous	Continuous
Pomona	Continuous	Continuous
Gulford College	8:00 AM to 5:00 PM	Closed
Kernersville	7:15 AM to 5:15 PM	Closed
Winston-Salem	Continuous	Continuous
Rural Hall	8:00 AM to 5:00 PM	Closed
Siloam	7:00 AM to 4:00 PM	Closed
Crutchfield	8:00 AM to 5:00 PM	Closed
Elkin	8:00 AM to 5:00 PM	Closed
Ronda	7:00 AM to 4:00 PM	Closed
Roaring River	7:30 AM to 4:30 PM	Closed
North Wilkesboro	8:00 AM to 5:00 PM	Closed
Statesville	Continuous	Continuous
Clemmons	8:00 AM to 5:00 PM	Closed
Mocksville	7:30 AM to 4:30 PM	Closed
Woodleaf	8:00 AM to 5:00 PM	Closed
Barber	Continuous	Continuous
Mt. Ulla	8:00 AM to 5:00 PM	Closed
Mooreville	7:00 AM to 10:00 PM	Closed
Davidson	7:00 AM to 5:00 PM	Closed
Cornelius	8:00 AM to 5:00 PM	Closed
Huntersville	7:30 AM to 4:30 PM	Closed
Airline Junction	Continuous	Continuous
Charlotte	Continuous	Continuous
Mt. Airy	8:00 AM to 5:00 PM	Closed
Pilot Mountain	8:00 AM to 5:00 PM	Closed
Walnut Cove	7:45 AM to 4:45 PM	Closed
Stokesdale	7:45 AM to 4:45 PM	Closed
Liberty	8:00 AM to 5:00 PM	Closed
Staley	8:00 AM to 5:00 PM	Closed
Siler City	7:30 AM to 5:30 PM	Closed
Bonlee	8:00 AM to 5:00 PM	Closed
Coldston	7:30 AM to 4:30 PM	Closed
Gulf	8:00 AM to 5:00 PM	Closed
Sanford	8:00 AM to 7:30 PM	Closed
	7:30 AM to 11:30 AM	Sat. Closed Sun.
Franklinville	7:30 AM to 4:30 PM	Closed
Rameur	8:00 AM to 5:00 PM	Closed

THE NAMES AND LOCATIONS OF LOCAL SURGEONS ARE:

O. L. Miller (Consultant Orthopedist)	Charlotte, N. C.
Thomas D. Sparrow	Charlotte, N. C.
R. I. Gibbon (Retired Consultant)	Charlotte, N. C.
B. K. Blalock	North Charlotte, N. C.
James W. Gibbons (Asst.)	Charlotte, N. C.
P. M. King (Asst.)	Charlotte, N. C.
J. G. Johnston (Oculist)	Charlotte, N. C.
H. C. Neblett (Assistant Oculist)	Charlotte, N. C.
J. W. MacConnell	Davidson, N. C.
Harry L. Johnson	Elkin, N. C.
H. H. Ogburn (Consultant)	Greensboro, N. C.
Shahane R. Taylor (Oculist)	Greensboro, N. C.
Horace G. Strickland (Oculist)	Greensboro, N. C.
R. N. Harden	Greensboro, N. C.
E. W. Vaughan (Asst. Surgeon)	Greensboro, N. C.
R. H. Whitaker	Kernersville, N. C.
L. P. Martin	Mocksville, N. C.
G. W. Taylor	Mooreville, N. C.
M. S. Martin	Mt. Airy, N. C.
F. C. Hubbard	N. Wilkesboro, N. C.
T. V. Goode	Statesville, N. C.
F. L. Knight	Sanford, N. C.
W. L. Patman	Siler City, N. C.
A. de T. Valk	Winston-Salem, N. C.
Henry L. Valk (Consultant)	Winston-Salem, N. C.
T. W. Davis (Oculist)	Winston-Salem, N. C.
B. N. Jones (Assistant Oculist)	Winston-Salem, N. C.
Robert A. Moore (Consultant Orthopedist)	Winston-Salem, N. C.

SOUTHERN RAILWAY SYSTEM

EASTERN LINES

Winston-Salem Division

TIME TABLE No.

79

Effective 12:01 A.M. (Eastern Time)

MONDAY, SEPTEMBER 25, 1950

FOR THE GOVERNMENT OF EMPLOYEES ONLY

G. W. ADAMS General Manager
 T. C. BLACKWELL, Gen. Superintendent Transportation
 B. L. STANFIEL Superintendent

POMONA—WINSTON-SALEM—WESTBOUND

Miles from Pomona	Station Nos	TIME TABLE NO. 79		FIRST CLASS				THIRD CLASS	
		In effect		15	1	21	5	71	73
		September 25, 1950							
STATIONS		Lv.	A.M.	A.M.	A.M.	P.M.	A.M.	P.M.	
.....	284	WYX... GREENSBORO.....N	2 40	7 05	10 00 ¹⁰	9 45 ¹⁶	
0.0	287	X { WYTCO POMONAN	2 45	7 10	10 05 ⁷¹	9 50	10 20 ²¹	8 45	
1.2	K 4	X { TERRA COTTAN	2 47	7 12	10 08	9 53	10 25	8 50	
3.4	K 7	X { GUILFORD COLLEGE...D	2 51	7 17	10 12	9 57	10 30	8 56	
6.7	K 10	X { FRIENDSHIPD	2 56	7 23	10 17	10 02	10 45	9 08 ¹⁶	
14.4	K 17	X KERNERSVILLE ...D	3 07	7 34 ⁷⁰	10 28	10 13	11 05	9 30	
19.4 GUTHRIED	3 13	7 45	10 36	10 22 ⁸	11 15	9 43	
23.5	X { WCTO SALEM YARDP	3 19	7 52	10 43	10 28 ⁷³	11 30	10 00 ⁸	
24.4	K 29	X { .. WINSTON-SALEM ..PN	3 20	7 55 ¹³	10 45	10 30	
		(Union Station) Ar.	A.M.	A.M.	A.M.	P.M.	A.M.	P.M.	
			Daily	Daily	Daily	Daily	Ex. Sun.	Daily	
			15	1	21	5	71	73	

The schedule figures between Pomona and Greensboro are for information only; the time tables, rules and regulations of the Danville Division will govern.

WINSTON JUNCTION—NORTH WILKESBORO

WESTBOUND			Capacity of Tracks in Cars	Miles from Pomona	Station Nos	TIME TABLE NO. 79		EASTBOUND	
3rd CLASS	1st CLASS	In effect				1st CLASS	3rd CLASS		
September 25, 1950		STATIONS							
65	13	Lv.	14	64					
Ex. Sun.	Daily	Ar.	Daily	Ex. Sun.					
A. M.	A.M.	P.	P.M.	P.M.					
7 25	8 23	4 33 ²²	2 10					
7 32	8 29	25 9 K 30	4 23	2 00					
7 40	8 34	X { WINSTON JUNCTION ...P	4 16	1 50					
8 00	8 48 ALSPAUGHD	4 06	1 35					
8 10	8 55	29 3 BETHANIAD	3 56	1 05					
8 20	9 03	7 33.0 K 38	3 48	12 50					
8 45	9 19	37 38 3 K 41	3 30	12 30					
9 00	9 29	X RURAL HALLD	3 19	12 15					
9 15	9 40	9 42 9 K 46	3 07	12 00					
9 35 ¹³	10 10 ⁶⁵	19 47.5 K 51	2 45	11 30 ¹³					
10 30 ⁶⁴	10 22	40 57.7 K 61	2 26	9 45 ⁶⁵					
10 45	10 30	10 64.4 K 67	2 26	9 30					
11 00	10 37	17 70.3 K 73	2 18	9 10					
11 10	10 50	X CRUTCHFIELDD	2 11	8 56					
11 30	10 50	90 80.7 K 84	2 00	8 45					
A.M.	Daily	WX ELKIND	14	8 45					
Ex. Sun.	13	X RONDAD	A.M.					
65	13	20 90.8 K 94	Ex. Sun.					
	 ROARING RIVERD	64					
		94.8 K 98						
		222 100.1 K 103						
		WXT NORTH WILKESBORO ...D						
		Ar.						
		Lv.						

No. 13 is Superior to No. 14 Winston-Salem to North Wilkesboro.

WINSTON-SALEM—POMONA—EASTBOUND

WINSTON-SALEM 3

Capacity of Tracks in Cars		TIME TABLE NO. 79 In effect September 25, 1950	FIRST CLASS				THIRD CLASS	
Siding	Other		10 Daily	22 Daily	16 Daily	8 Daily	70 Ex. Sun.	72 Daily
		STATIONS	A.M. 9 30 ²¹	P.M. 6 15	P.M. 9 25 ⁵	P.M. 11 00	A.M.	P.M.
		Ar. WYX.. GREENSBORO.....N						
		2.8						
	Yard	X { WYTCO POMONAN	f 9 22	6 07	9 18	10 52	8 30	8 05
	10	1.2 TERRA COTTA.....	f 9 20	6 04	9 16	10 50	8 25	7 59
	8	2.2 GUILFORD COLLEGE...D	s 9 15	5 59	9 13	11 0 45	8 20	7 54
	58	3.3 X { FRIENDSHIP.....	f 9 10	5 54	9 08 ⁷³	11 0 40	8 00	7 46
	50	7.7 X { KERNERSVILLE...D	s 8 59	5 44	8 58	10 29	7 34 ¹	7 26
		5.0						
		GUTHRIE.....	f 8 52	5 36	8 52	10 22 ⁵	6 55	7 13
	Yard	4.1 X { WCTO SALEM YARD...P	8 46	5 31	8 46	10 16 ⁷³	6 45	7 00
		0.8						
		WINSTON-SALEM...N (Union Station)	8 45	5 30	8 45	10 15		
		Lv.	A.M.	P.M.	P.M.	P.M.	A.M.	P.M.
			Daily 10	Daily 22	Daily 16	Daily 8	Ex. Sun. 70	Daily 72

The schedule figures between Pomona and Greensboro are for information only; the time tables, rules and regulations of the Danville Division will govern.

MOORESVILLE JCT.—STATESVILLE

SOUTHBOUND				NORTHBOUND					
THIRD CLASS		Capacity of Tracks in Cars		Miles from Charlotte	Station Nos.	TIME TABLE NO. 79 In effect September 25, 1950		THIRD CLASS	
59 Daily	61 Ex. Sun.					62 Ex. Sun.	58 Daily		
P.M. 10 15	P.M. 12 01	71	44.0	S 28	Lv. WYX.....	Ar. STATESVILLE.....N	A.M. 11 15	P.M. 9 20	
	12 15	4	39.8	O 40	4.2 BARIUM SPGS.		11 02		
10 36	12 20	10	38.3	O 88	X.....	1.5 TROUTMANS	10 55	9 10	
11 10	12 40		29.1	O 29	Ar. WYX..	Lv. MOORESVILLE JCT.	10 30	8 50	
P.M. 59	P.M. 61						A.M. 62	P.M. 58	

CLIMAX—RAMSEUR

WESTBOUND				EASTBOUND					
THIRD CLASS		Capacity of Tracks in Cars		Miles from Climax	Station Nos.	TIME TABLE NO. 79 In effect September 25, 1950		THIRD CLASS	
77 Ex. Sun.	76 Ex. Sun.					76 Ex. Sun.	77 Ex. Sun.		
A.M. 9 20 ⁷⁶	9 30	34	18.7	CR 19	Lv. TX.....	Ar. RAMSEUR.....D	A.M. 8 50 ⁷⁷	8 40	
9 38	10 20	25	16.2	CR 16	2.5 FRANKLINVILLE.....D		8 35		
	A.M. 77	9	14.1	CR 14	W.....	14.1 CEDAR FALLS	7 50		
Ex. Sun. 77		19	0.0	CF 82	Ar. X.....	Lv. CLIMAX	A.M. 76		

WINSTON-SALEM—CHARLOTTE—SOUTHBOUND

Miles from Winston-Salem	Station Nos.	TIME TABLE NO. 79 In effect September 25, 1950 STATIONS	FIRST CLASS			THIRD CLASS				
			15 Daily	13 Daily	21 Daily	59 Daily	65 Ex. Sun.	69 Ex. Sun.	61 Ex. Sun.	53 Daily
			A.M.	A.M.	A.M.	P.M.	A.M.	A.M.	P.M.	P.M.
.....	K 29 WINSTON-SALEM (Union Station) Lv. PN	3 30	8 20 ¹	11 00	7 15 ⁶⁹	7 30 ⁶⁵	9 20
0.1	0.1 W. S. S. B. CROSSING
1.5	K 30	X { 1.4 WINSTON JUNCTION P	3 34	8 23	11 05	7 25	7 40	9 30
5.0	L 8	3.5 HANES	A.M.	11 12	A.M.
6.5	L 5	1.6 FRONTIS 7.4	3 42	11 14	7 50	9 40
13.9	L 12 CLEMMONS D	3 55	11 26	8 05	9 55
18.1	L 17	4.2 ADVANCE	4 02	11 33	8 14	10 04
20.9	L 20	2.8 BIXBY	4 06	11 37	8 20	10 10
22.6	L 21	1.7 CORNATZER	11 41	8 25	10 15
27.7	L 27	X { 5.1 MOCKSVILLE D	4 19	11 52	8 50	10 30
32.7	L 31	5.0 WX { COOLEEMEE JCT.	4 26	12 05 ⁶⁸	9 15	10 42
35.8	L 34	3.1 X { WOODLEAF D	4 31	12 15	9 27	10 49
38.2	0.4 HARDAWAY QUARRY
41.0	S 11	4.8 WYX { BARBER N	4 40	12 40 } 1 00 }	9 50	11 40 ⁵²
45.3	L 44	4.3 BEAR POPLAR 2.6	A.M.	1 07	A.M.
47.9	L 47 MT. ULLA D	1 12	11 55
51.8	3.9 MAZEPPA	1 18	P.M.	P.M.
55.0	O 29	3.2 X { WY.. MOORESVILLE JCT.	1 23	11 10	12 40	12 05
55.8	O 28	0.8 MOORESVILLE NC	1 28	11 13	12 50	12 40
59.5	O 25	3.7 MOUNT MOURNE	1 34	11 27	12 58	12 50
62.6	O 22	3.1 X { DAVIDSON D	1 39	11 38	1 10	1 10
63.9	O 21	1.3 CORNELIUS D	1 43	11 43	1 19	1 25
66.6	O 18	2.7 CALDWELL	1 47	11 53	1 25	1 32
69.2	O 15	X { 2.6 HUNTERSVILLE D	1 53	12 03	1 34	1 45
74.3	O 10	5.1 CROFT	2 03	12 22	1 45	1 55
78.8	O 5	4.5 DERITA	2 15 ²²	12 40	1 56	2 05
81.4	2.6 ATANDO JCT.	2 18 ⁶¹	12 50	2 01 ²² 21	2 15
83.5	X { WCTYO AIR LINE JCT. N	1 00	2 10	2 20
83.5	2.1 S.A.L.R.R. CROSSING	2 24
84.1	380	0.6 W. CHARLOTTE N (Trade St.) Ar.	A.M.	A.M.	2 30 P.M.	A.M.	A.M.	A.M.	P.M.	A.M.
			Daily 15	Daily 13	Daily 21	Daily 59	Ex. Sun. 65	Ex. Sun. 69	Ex. Sun. 61	Daily 53

CHARLOTTE—WINSTON-SALEM—NORTHBOUND

Capacity of Tracks in Cars		TIME TABLE NO. 79 In effect September 25, 1950	FIRST CLASS			THIRD CLASS				
Siding	Other		STATIONS	14 Daily	22 Daily	16 Daily	64 Ex. Sun.	68 Ex. Sun.	62 Ex. Sun.	58 Daily
		Ar. PN WINSTON-SALEM (Union Station) 0.1	P.M. 4 40	P.M. 5 10	P.M. 8 35	P.M. 2 20	P.M. 2 00	A.M.	P.M.	A.M. 2 20
	X	1.4 W. S. S. B. CROSSING								
		PN WINSTON JUNCTION	4 33 ²²	5 02 ¹⁴	8 31	2 10 ⁶⁸	1 47 ⁶⁴			2 10
	11	3.5 HANES	P.M.	4 52		P.M.				
51		1.5 FRONTIS		4 50	8 24		1 32			1 55
		7.4								
	40	D CLEMMONS		4 40	8 13		1 12			1 35
	12	4.2 ADVANCE		4 31	8 06		12 56			1 25
	25	2.8 BIXBY		4 25	8 00		12 48			1 15
	7	1.7 CORNATZER		4 21			12 42			1 10
50	62	X 5.1 MOCKSVILLE		4 12	7 49		12 30			12 55
	47	5.0 WX COOLEEMEE JCT.		4 00	7 42		12 05 ²¹ 11 35			12 40
		3.1 WOODLEAF		3 54	7 37		11 20			12 30
	35	X 0.4 HARDAWAY QUARRY								
	53	4.8 WYX BARBER		3 45 3 30	7 30		11 00			12 10 10 50 ⁵³
	6	4.3 BEAR POPLAR		3 18	P.M.		A.M.			
	37	D 2.8 MT. ULLA		3 13						10 32
	4	3.9 MAZEPPA		3 07				A.M.	P.M.	
		3.2 X WY MOORESVILLE JCT.		3 03			10 30		8 50	10 15
25	96	0.8 MOORESVILLE		3 01			10 26		8 48	10 10
	8	3.7 MOUNT MOURNE		2 49			10 18		8 42	9 53
	38	3.1 X DAVIDSON		2 43			10 08		8 36	9 47
	24	1.3 CORNELIUS		2 38			10 02		8 31	9 42
	72	2.7 CALDWELL		2 34				9 52	8 25	9 36
	20	X 2.6 HUNTERSVILLE		2 30				9 43	8 20	9 30
	75	5.1 CROFT		2 22				9 28	8 10	9 20
	69	4.5 DERITA		2 15 ²¹				9 15	7 55	9 11
		2.8 ATANDO JCT.		2 10 ⁶¹				9 08	7 50	9 05
	Yard	X 2.1 WCTYO AIR LINE JCT.		2 05				9 00	7 45	9 00
		0.8 S. A. L. R. R. CROSSING		2 00						
		N W CHARLOTTE (Trade St.)	P.M.	P.M.	P.M.	P.M.	A.M.	A.M.	P.M.	P.M.
		Lv.	Daily 14	Daily 22	Daily 16	Ex. Sun. 64	Ex. Sun. 68	Ex. Sun. 62	Daily 58	Daily 52

SANFORD—MT. AIRY—WESTBOUND

Miles from Mt. Airy	Station Nos.	TIME TABLE NO. 79 In effect September 25, 1950 STATIONS	THIRD CLASS							
			75	77		79	81	83	85	
			Ex. Sun.	Ex. Sun.		Ex. Sat. and Sun.	Ex. Sun. and Mon.	Sat. and Mon only	Sat. and Mon only	
			A.M.	A.M.		A.M.	A.M.	P.M.		
130.1	CF130	WYCX. SANFORD Lv. D					8 30	1 00		
		6.5								
123.6	CF124 CUMNOCK					8 45	1 15		
		2.8								
120.8	CF121	XY..... GULF D					8 55	1 25		
		3.5								
117.2	CF117	X..... GOLDSTON D					9 10	1 40		
		8.9								
113.3	CF113 BEAR CREEK					9 20	1 50		
		2.6								
110.7	CF111 BONLEE D					9 27 ⁸²	1 57		
		1.5								
109.2	CF109	W MT. VERNON SPRINGS .					9 32	2 02		
		4.5								
104.7	CF105	X..... SILER CITY D					10 00 ⁸⁰	2 30		
		7.5								
97.2	CF 97 STALEY D					10 15	2 45		
		W 4.5								
92.7	CF 93	X..... LIBERTY D					10 30	3 00		
		7.1								
85.6	CF 86 JULIAN		A.M.			10 45	3 15		
		3.4								
82.2	CF 82	X..... CLIMAX		10 20 ⁸¹			10 55 ⁷⁷	3 25		
		4.9								
77.3	CF 77	.. PLEASANT GARDEN ..		10 30			11 05	3 35		
		3.6								
73.7	CF 74 VANDALIA	A.M.	10 40		A.M.	11 15	3 45	A.M.	
		4.3								
69.4	CF 70	WYCXGREENSBORO .PN.	3 30	10 50		8 30	11 40	4 10	7 30 ⁷⁶	
		6.2								
63.2	CF 63 BATTLE GROUND ...	3 50	A.M.		9 00	A.M.	P.M.	7 59	
		6.7								
57.5	CF 58 SUMMERFIELD	4 00			9 15			8 13	
		6.2								
51.3	CF 51 STOKESDALE D	4 15			9 30			8 27	
		3.3								
43.0	CF 43	W..... MATA	4 25			9 45			8 41	
		1.9								
46.1	CF 46 BELEWS CREEK	4 30			9 55			8 50	
		6.0								
40.1	CF 40	YX.. WALNUT COVE ... D	5 00 ⁷⁶			10 25			9 19	
		5.6								
34.5	CF 35 GERMANTON	A.M.			10 45 ⁷⁸			9 38	
		4.6								
29.9	CF 30	WX.. RURAL HALL D				11 10			10 00	
		4.8								
25.1	CF 25 KING				11 25			10 15 ⁷⁸	
		6.0								
19.1	CF 19 PINNACLE				11 50			10 40	
		4.7								
14.4	CF 14	... PILOT MOUNTAIN ... D				12 10			11 00	
		6.0								
8.4	CF 8 ARARAT				12 30			11 20	
		8.4								
0.0	CF 0	WYCX MT. AIRY D				12 55 ⁸⁴			11 45	
		Ar.	A.M.	A.M.		P.M.	A.M.	P.M.	A.M.	
			Ex. Sun.	Ex. Sun.		Ex. Sat. and Sun.	Ex. Sun. and Mon.	Sat. and Mon only	Sat. and Mon only	
			75	77		79	81	83	85	

MT. AIRY—SANFORD—EASTBOUND

Capacity of Tracks in Cars		TIME TABLE NO. 79 In effect September 25, 1950		THIRD CLASS								
Siding	Other	STATIONS		76 Ex. Sun.	80 Ex. Sat. and Sun.		78 Ex. Sun. and Mon.	82 Sat. and Mon only	84 Sat. and Mon only			
			Ar. D	A.M.	A.M.		P.M.	A.M.				
	Yard	WYCX.	SANFORD		11 15			10 32				
	14		CUMNOCK		10 55			10 12				
	38	XY	GULF	D	10 45			10 02				
	30	X	GOLDSTON	D	10 37			9 54				
	19		BEAR CREEK		10 27			9 44				
	27		BONLEE	D	10 20			9 27 ⁸¹				
			W. MT. VERNON SPRINGS.		10 15			9 19				
	54	X	SILER CITY	D	10 00 ⁸¹			9 03				
	20		STALEY	D	9 40			8 49				
	28	X	LIBERTY	D	9 20			8 39				
	13		JULIAN		A.M.	9 01		8 21				
	19	X	CLIMAX		7 50	8 50		8 10				
	14		PLEASANT GARDEN		7 40	8 30		7 58				
	11		VANDALIA		7 30	8 15	P.M.	7 48	P.M.			
	Yard	WYCX	GREENSBORO	PN	7 20 ⁸² 7 00 ⁸⁵	8 00 ⁸²	1 10	7 30 ⁷⁶ 80	5 10			
	17		BATTLE GROUND		6 40	A.M.	12 40	A.M.	4 40			
	26		SUMMERFIELD		6 20		12 20		4 20			
	22		STOKESDALE	D	6 00		12 03		4 03			
		W	MATA		5 50		11 45		3 45			
	8		BELEWS CREEK		5 45		11 35		3 35			
	90	YX	WALNUT COVE	D	5 30 ⁷⁵		11 10		3 10			
	19		GERMANTON		A.M.		10 45 ⁷⁹		2 45			
	61	WX	RURAL HALL	D			10 30		2 30			
	19		KING				10 15 ⁸⁵		2 15			
	34		PINNACLE				9 55		1 55			
	26		PILOT MOUNTAIN	D			9 40		1 40			
	15		ARARAT				9 25		1 25			
	Yard	WYCX.	MT. AIRY	D Lv.	A.M.	A.M.	9 00 A.M.	A.M.	1 00 ⁷⁹ P.M.			
		No. 75 is superior to No. 76 Greensboro to Walnut Cove, and No. 85 is superior to No. 84, Greensboro to Mt. Airy.		Ex. Sun.	Ex. Sat. and Sun.		Ex. Sun. and Mon.	Sat. and Mon only	Sat. and Mon only			
				76	80		78	82	84			

SPECIAL INSTRUCTIONS

1. The Special Instructions do not relieve employes from proper protection of the train according to Rule 99.

2. SUPERIOR DIRECTION

All regular north and eastbound trains are superior to trains of the same class moving in the opposite direction in accordance with Rule 72, except as follows:

No. 13 is superior to No. 14 Winston-Salem to North Wilkesboro. No. 75 is superior to No. 76, Greensboro to Walnut Cove. No. 85 is superior to No. 84, Greensboro to Mt. Airy.

3. JOINT TRACKAGE

Trains and engines of Winston-Salem Division will use the tracks of other Divisions in accordance with their time tables, rules and regulations as follows:

Between Pomona and Greensboro	Division Danville
Ninth Street and Trade Street, Charlotte.....	Charlotte

4. ADDITIONAL INITIAL AND CLEARANCE CARD STATIONS

(Rules 4, 84, 1141 and 1301)

A train must receive a clearance card before leaving its initial station.

Trains must receive clearance cards at additional stations as follows:

Winston-Salem Union Station, all trains.
Barber, all trains.

5. BULLETIN BOARDS AND SPECIAL ORDER BOOKS

(Rules 111, 1142, 1302 and 1387)

Greensboro, Pomona, Salem Yard, Winston-Salem Union Station, N. Wilkesboro, Statesville, Charlotte, Mt. Airy and Sanford.

6. TRAIN REGISTERS

(Rules 83 and 1143)

Pomona, Salem Yard, Winston-Salem Union Station, Winston Junction, North Wilkesboro, Charlotte, Atando Jct., Air Line Jct., Mooresville Jct., Barber, Statesville, Coolee-mee Jct., Mt. Airy, Walnut Cove, Greensboro, Climax, Ramseur, and Sanford.

Wilkesboro Line trains and train No. 21 will register at Winston Jct.

First class trains will register at Pomona with Form 721.

7. STANDARD CLOCKS

(Rule 3)

Greensboro, Salem Yard, N. Wilkesboro, Winston-Salem, (Dispatchers' Office) Air Line Jct., Charlotte, and Mt. Airy.

8. RAILROAD CROSSINGS AT GRADE

Interlocked (Rules 98, 601 to 671)

Winston-Salem, N. C.	WSSB.
Barber, N. C.	Asheville Division.
Walnut Cove, N. C.	N. & W. Ry.

Not Interlocked (Rule 98)

Charlotte, N. C.	S. A. L. Ry.
Gulf, N. C.	N. S. Ry.
Sanford, N. C.	S. A. L. Ry.

9. JUNCTIONS

Interlocked (Rules 98, 601 to 671)

Pomona, N. C.	Danville Division.
Walnut Cove, N. C.	N. & W. Ry.

Not Interlocked (Rule 98)

Winston-Salem Union Passenger Station	Norfolk and Western Rwy.
Winston-Junction, N. C.	Wilkesboro & Charlotte Lines
Rural Hall, N. C.	Wilkesboro and Mt. Airy Lines

Statesville, N. C.	Asheville Division.
Mooresville Jctn., N. C.	Statesville Branch.
Air Line Jctn., N. C.	Charlotte Division.
Charlotte, N. C. (9th St.)	Charlotte Division.
Atando Junction, N. C.	Cut off.
Greensboro, N. C.	Danville Division
Climax, N. C.	Ramseur Branch
Gulf, N. C.	N. S. Ry.
Sanford, N. C.	S. A. L. Ry.
Sanford, N. C.	A. C. L. Ry.
Sanford, N. C.	A. & W. Ry.

10. YARD LIMITS

(Rule 93)

"X" opposite station name indicates yard limits.

11. ENTRANCE SWITCH TO SIDINGS AND OTHER TRACKS

(Rules 88 to 90)

Unless otherwise provided enter at first switch of first siding. When a train which is to hold the main track is first to arrive at meeting point, fixed by train order, switch must be properly set for opposing train to enter siding.

12. MAXIMUM SPEED RESTRICTIONS

(Rules 108 and 1305)

Between Pomona and Winston-Salem

Passenger trains 55 miles per hour. Freight trains 45 miles per hour.

Between Winston-Salem and Barber

Passenger trains 50 miles per hour. Freight trains 40 miles per hour.

Between Barber and Charlotte

Passenger trains 55 miles per hour. Freight trains 40 miles per hour.

Between Winston-Salem and N. Wilkesboro

Passenger trains 45 miles per hour. Freight trains 35 miles per hour.

Between Mooresville Junction and Statesville

Freight trains 40 miles per hour.

Between Mt. Airy and Sanford

Freight trains 30 miles per hour.

Between Climax and Ramseur

Freight trains 20 miles per hour.

These speeds must be further reduced on curves where conditions require it to insure safe and comfortable movement.

The maximum speed of freight trains handling loaded hopper bottom coal cars, or flat cars loaded with creosoted poles, or gondolas loaded with lumber that extends above the sides of the car, will be forty (40) miles an hour. Except Mt. Airy, Sanford Line thirty (30) miles an hour, Ramseur Branch fifteen (15) miles an hour.

Engines without cars will be governed by speed according to class of engines.

Trains or engines must not exceed 15 miles an hour entering or leaving sidings or moving through crossovers or turnouts; except where turnout is No. 16 or over, speed of 20 miles an hour must not be exceeded.

Unless otherwise restricted, trains will not exceed maximum speed on curves as shown below:

	Miles per hour	
	Passenger	Freight
WINSTON JUNCTION-BARBER		
Between MP L-1.0 & MP L-1.4	30	15
L-10.2 & MP L-10.5	45	35
L-14.1 & MP L-14.9	30	25
L-15.8 & MP L-15.9	45	35
L-20.5 & MP L-21.7	35	30
L-23.6 & MP L-24.4	30	25

WINSTON-SALEM-NORTH WILKESBORO:

Between MP K-43.7 & MP K-43.9	35	30
K-46.8 & MP K-47.2	35	30
K-52.8 & MP K-53.0	35	30
K-70.7 & MP K-71.1	35	30
K-83.7 & MP K-83.9	35	30
K-87.7 & MP K-87.9	35	30
K-93.2 & MP K-93.4	35	30

WINSTON-SALEM 10

The red aspect must also be displayed when a train crosses over, or is using opposite main track against current of traffic—or on single track when such train fails to clear main track in accordance with the rules.

Opposing trains observing this emergency red light must stop immediately and not proceed until the way is known to be clear.

The red light is an additional precaution and does not relieve train and enginemen from full compliance with Rules 99 and 102.

Instructions Covering Movement of Sperry and A.A.R. Rail Test Cars.

1. When rail test cars are testing rail, flag protection must be provided to the rear.

2. In territory where trains operate by signal indication in accordance with Rule 261, the dispatcher or operator must be acquainted with proposed movement of a rail test car and not permit an opposing train to enter the block occupied by a rail test car. CTC dispatchers and remote control operators must tag or obstruct levers which govern opposing movement of trains into the block occupied by a rail test car, and the tag or obstructing peg must not be removed until the car is clear of the block.

3. When a rail test car is to test rail within interlocking limits, levermen must be notified of the movement and Rules 616 and 617 complied with so that levers affecting movement of the car will not be manipulated until the car has passed beyond interlocking limits.

4. When testing rail, rail test cars must approach all high-way-railroad grade crossings which are protected by flashing light signals or automatic gates prepared to stop unless it is known that such protective devices are operating.

5. When not testing rail, rail test cars must be handled in accordance with rules applying to other train movements.

15. ADDITIONAL FLAG STOPS

(Rules 16d and 28)

Colfax.....	Nos. 1, 5, 8 and 10	Burch.....	Nos. 13 and 14
Boyd.....	Nos. 13 and 14	Jopler.....	Nos. 21 and 21
Limerock.....	Nos. 13 and 14		
Shoal.....	Nos. 13 and 14		

16. HELPING TRAINS

(Rule 1657)

When it is necessary for a train to push another train on a grade or into a siding, the pusher engine must be detached from its train, after proper measures have been taken for its protection, including setting of hand brakes and such other measures as may be necessary, and after coupling to the rear car of the train to be pushed, the air hose must be coupled and the air operated through; the air pressure must be equalized between the pushing engine and the train to be pushed, and the cut out cock under automatic brake valve closed. This automatically cuts out train control operation on the pusher engine.

When the pusher engine is uncoupled from the train, cut out cock under brake valve must be opened so as to make train control operative.

Position of brake valve handles on the pushing engine to be the same as the second engine on a double header train, and the instructions in books of rules governing the operation of a train with two or more engines, including air brake handling, will govern.

17. AIR BRAKE INSTRUCTIONS TO ENGINEMEN AND TRAINMEN (Rules 1650 to 1675)

When brakes are applied in any manner except by engineer's brake valve, close throttle, place automatic brake valve on lap and allow it to remain on lap until train comes to a stop.

The application of brakes in this manner will be indicated by—Steam Locomotives—Pressure on brake cylinder air gauge, train pulling hard or slowing down.

Diesel-Electric Locomotives—Brake cylinder pressure on air gauge, train pulling hard, speed indicator falling in miles per hour, or transition indicator moving to the red.

If necessary to prevent sliding of driving wheels, the driving brake cylinder pressure can be graduated with the independent brake valve.

When an emergency application is made, allow automatic brake valve to remain on lap at least two (2) minutes before releasing.

When train is stopped under such circumstances, it must not proceed until proper signal is given.

Before giving signal to proceed, trainmen must know the brakes are released and pressure is being restored.

18. SPRING SWITCHES

(Rules 517 and 1642 to 1645)

When any part of a train is moving through a spring switch the speed must not exceed fifteen miles per hour, except at the ends of double track where speed must not exceed twenty miles per hour.

Spring switches are located as follows:

East end Lead track Salem Yard—

Trailing movements may be made through these switches without opening or closing by hand, but in case a train is stopped before passing entirely through the switch, it must not be backed, unless switch is opened or set to siding by hand.

"S S" signs are located adjacent to spring switches, and will also, when practicable, indicate the location of clearance point for adjacent track, unless "Clear This Post" sign is used.

WHEN NECESSARY, PASSENGER TRAINS WILL WAIT FOR CONNECTIONS AS INDICATED BELOW. SUPERINTENDENT OR CHIEF DISPATCHER WILL INSTRUCT IN CASES OF UNUSUAL CONDITIONS OR EMERGENCIES.

Train No.	Wait At	For	Time
1	Greensboro	Danville Div.	39 2 hours 30 minutes
5	Greensboro	Danville Div.	35 1 hour Note 2
5	Greensboro	Danville Div.	38 25 minutes Note 2
15	Greensboro	Danville Div.	31 Indefinitely
15	Greensboro	Danville Div.	111 30 minutes
21	Greensboro	Danville Div.	33 15 minutes Note 2

Note 2—When passengers are reported.

BUSINESS TRACKS AND STATIONS NOT SHOWN AS STATIONS ON TIME TABLE

Name	Location	Name	Location
Muddy Creek	Mile L 8.5	Mojoson	Mile CF 53.6
Iredell County		Guilquarry	Mile CF 53.7
Home	Mile O39.3	Sears	Mile CF 65.5
Colfax	Mile K10.6	Capyco	Mile CF 96.2
Tiretown X	Mile K28.3	Borens	Mile CF120.0
Shoal	Mile K53.7	Orten	Mile CF120.0
Byrds Siding	Mile K59.4	Womack	Mile CF127.7
Abole	Mile K73.0	Pools	Mile CF129.0
Burch	Mile K74.5	Millboro	Mile CR 9.5
		Cedar Fall	
		Factory	Mile CR 13.6
		Franklin Cotton House	Mile CR 15.7

DIVISION OFFICERS

E. E. LOVING, Trainmaster	Winston-Salem
A. H. GRAHAM, Division Engineer	Winston-Salem
E. K. McARTHUR, Asst. Division Engineer	Greensboro
F. J. FELKER, Chief Dispatcher	Winston-Salem
J. T. FOX, Dispatcher	Winston-Salem
W. S. ROTHROCK, Dispatcher	Winston-Salem
H. F. BOUKNIGHT, Dispatcher	Winston-Salem
S. E. ADCOCK, Dispatcher	Winston-Salem
P. MURRAY, Dispatcher	Winston-Salem
W. S. ANGEL, General Road Foreman Eng.	Spencer

LOCOMOTIVE RATING IN TONS OF 2,000 POUNDS EXCLUSIVE OF TENDER AND CABOOSE

		1500 H.P. Diesel Road Switcher	Mikado 4500-4700 CNO & TP 6200	Mikado 4800-4914			Consolidated 251-556 Inclusive	Superheated Consolidated 567-8338 Inclusive
N. Wilkesboro	to Elkin	1800			Mt. Airy	to Greensboro		750
Elkin	" Donnaha	2400			Greensboro	" Sanford	990	1200
Donnaha	" Rural Hall	1375			Climax	" Ramseur	800	
Rural Hall	" Winston-Salem	1475						
Winston-Salem	" Friendship	1800	1750	2000				
Friendship	" Pomona	2400	2300	2600				
Mocksville	" Winston-Salem	1300	1400					
Barber	" Mocksville	1800	1700					
Air Line Jct.	" Barber	2100	2000					
Air Line Jct.	" Statesville	1775	2000	2500				
Pomona	" Friendship	2300	2300	2600	Ramseur	" Climax	600	
Friendship	" Winston-Salem	1800	1750	2000	Sanford	" Liberty		1200
Winston-Salem	" Donnaha	1375			Liberty	" Greensboro	1120	1300
Donnaha	" Elkin	2400			Greensboro	" Mt. Airy		750
Elkin	" N. Wilkesboro	1500						
Winston-Salem	" Mocksville	1375	1300					
Mocksville	" Barber	1700	1625					
Barber	" Mooresville	2100	2000					
Statesville	" Mooresville	2600	2650	3150				
Mooresville	" Air Line Jct.	3500	3500	4000				

The above rating is based on maximum grades and may be increased over certain parts of the line when necessary. In making computation less than 1,000 lbs. will be dropped—1,000 lbs. will be counted one ton.

SYSTEM LOCOMOTIVES, DERRICKS, PILE DRIVERS AND OTHER ROADWAY EQUIPMENT AND SYSTEM AND FOREIGN CARS MAY BE OPERATED PROVIDED WEIGHTS AND OTHER RESTRICTIONS SHOWN BELOW ARE NOT EXCEEDED.

BETWEEN POMONA, WINSTON-SALEM AND MOORESVILLE

EQUIPMENT	TYPE	CLASS	TOTAL WEIGHT
Santa Fe Engines	2-10-2	378	(a) (c) 378,000
Mikado Engines	2-8-2	330	(a) (c) 329,500
Mikado Engines	2-8-2	292	292,500
Pacific Engines	4-6-2	305	(b) 300,000
Mountain Engines	4-8-2	327	327,000
Pasgr. Diesel Power Units	6-6		(d) 315,000
Freight Diesel Power Units	4-4		245,000
Loaded Cars	4-wheel trucks		210,000
Loaded Cars	6-wheel trucks		270,000

(a) May be operated between Pomona and Winston-Salem and beyond Winston-Salem to Cherry St. Underpass Mile L-0.5, but must not cross this structure. These engines must not be operated between Cherry St. Underpass, Winston-Salem, and Barber Junction, but may be operated in emergency detour movement between Barber Junction and Mooresville at a speed not exceeding 25 miles per hour.

(b) Permitted in detour movement only at speed not to exceed twenty-five miles per hour.

(c) Must not be handled over side or industrial tracks containing open deck trestles.

(d) Diesel power units may be operated in detour movement between Charlotte and Greensboro via Winston-Salem at a speed not exceeding 40 miles per hour.

All Engines permitted on this line may be operated coupled except Santa Fe engines which must not be operated coupled to each other, but may be operated coupled to engines of a lighter or smaller class between Pomona and Winston-Salem.

Derricks D-30, and D-40 may be operated at a speed not exceeding twenty miles per hour.

Derricks D-24, D-27, D-29, D-32, D-37, D-41, D-58, D-65,

D-66, D-67, D-68, D-69, and D-5994 may be operated at a speed not exceeding twenty-five miles per hour.

Derricks D-70, D-71, D-72, D-73, D-74 and D-5989 may be operated at a speed not exceeding 20 miles per hour between Pomona and the North end of Cherry Street Underpass, Mile L-0.5, but must not cross this structure, and from Mooresville to the South end of Northwest Blvd. Underpass, Mile L-1.2, but must not cross this structure. These derricks must not be operated over side tracks or industrial tracks containing open deck trestles.

BETWEEN CHARLOTTE AND STATESVILLE

EQUIPMENT	TYPE	CLASS	TOTAL WEIGHT
Mikado Engines	2-8-2	292	(d) 292,000
Santa Fe Engines	2-10-2	378-A	(a) (b) (c) 378,000
Mikado Engines	2-8-2	330	(a) (c) 329,500
Pacific Engines	4-6-2	305	(d) 300,000
Mountain Engines	4-8-2	327	(d) 327,000
Freight Diesel Power Units	4-4		(d) 245,000
Loaded Cars	4-wheel trucks		210,000
Loaded Cars	6-wheel trucks		270,000

(a) Must not exceed a speed of twenty-five miles per hour at any point and must not exceed ten miles per hour over the highway underpass Mile O.20.8.

(b) Must not be operated coupled to each other but may be operated coupled to engines of a lighter or smaller class.

(c) Must not be handled over side or industrial tracks containing open deck trestles.

(d) Must not exceed a speed of forty miles per hour at any point and must not exceed ten miles per hour over the highway underpass Mile O.20.8.

All System derricks may be operated, except that Derricks D-70, D-71, D-72, D-73, and D-5989 must not be operated over side tracks containing open deck trestles.

Derricks D-30, D-40, D-70, D-71, D-72, D-73, D-74,

WINSTON-SALEM 12

and D-5989 must not exceed a speed of twenty miles per hour, other derricks twenty-five miles per hour; except speed of all derricks should not exceed ten miles per hour over highway underpass, Mile O.20.8.

BETWEEN WINSTON JUNCTION AND NORTH WILKESBORO

EQUIPMENT	TYPE	CLASS	TOTAL WEIGHT
Freight Diesel Power Units	4-4		(b) (c) 245,000
Pacific Engs.	4-6-2	232	(b) 232,000
10-Wheel Pass. Engs	4-6-0	172	(a) 192,300
Consolidation Engs.	2-8-0	205	(a) 214,000
Loaded Cars			210,000

All engines permitted on this line may be operated coupled.

(a) Must not exceed a speed of twenty miles per hour over Mitchell River, Mile K-74.6, and Mulberry Creek, Mile K-97.2.

(b) Must not exceed a speed of ten miles per hour over the following structures:

- Mitchell River mile K-74.6
- Mulberry Creek mile K-97.2

(c) May be operated in multiple units between Winston Junction and Elkin only.

System derricks D-24, D-27, D-29, D-30, D-32 and D-58 may be operated at a speed not to exceed twenty miles per hour.

BETWEEN MT. AIRY AND SANFORD

EQUIPMENT	TYPE	CLASS	TOTAL WT.
Diesel Switch Engs.	4-4		(b) 242,000
Consolidation Engs.	2-8-0	205	(a) 214,000
Consolidation Engs.	2-8-0	170	170,000
Consolidation Engs.	2-8-0	158	158,000
Loaded Cars			210,000

All steam engines permitted on this line may be operated coupled.

(a) Consolidation stoker fired engines not exceeding 228,000 pounds may be operated between Greensboro and Sanford only. System Derricks D-24, D-27, D-29, D-30, D-33 and D-58 may be operated between Mt. Airy and Sanford at a speed not to exceed twenty miles per hour.

(b) Single units only may be operated.

BETWEEN CLIMAX AND RAMSEUR

EQUIPMENT	TYPE	CLASS	TOTAL WT.
Consolidation Engrs.	2-8-0	158	158,000
Loaded Cars			169,000

Engines permitted on this line must not be operated coupled.

System Derricks D-24, D-27, D-29 and D-30 may be operated at a speed not to exceed five miles per hour.

NOTE: The weight of engines shown above is weight exclusive of tender.

PILE DRIVERS

Between Pomona, Winston-Salem and Mooresville, or Charlotte and Statesville, PD-36, PD-24 and PD-25 may be operated with tender at one end and tool car weighing not exceeding 90,000 pounds gross at other end, at speed not in excess of the following: PD-36 thirty-five miles an hour; PD-24 and PD-25 twenty-five miles an hour; PD-36 must have stack removed in transit.

Between Winston-Salem and North Wilkesboro and between Mt. Airy and Sanford including Ramseur Branch PD-36, PD-24 and PD-25 may be operated with tender at one end and tool car weighing not exceeding 90,000 pounds gross at other end, at speed not in excess of following: PD-36 twenty-five miles an hour; PD-24 and PD-25 twenty miles an hour; PD-36 must have stack removed in transit.

LOCOMOTIVE CRANES

LC-6 and LC-35 can be handled over all main line and side tracks on entire Division. LC-34 can be handled over main tracks Pomona to Winston-Salem to Charlotte and between Mooresville junction and Statesville but must not be operated over side or industrial tracks containing open deck trestles.

VETERINARIANS

Cecil W. Parker	Charlotte, N. C.
G. C. Monroe	Greensboro, N. C.
W. A. Hornaday	Greensboro, N. C.
O. C. Lynch	Statesville, N. C.
James T. Dixon	Winston-Salem, N. C.

LIVESTOCK AGENTS

N. Moore, General Livestock Agent	Atlanta, Ga.
J. H. White, Livestock Agent	Columbia, S. C.

HOSPITALS

Good Samaritan Hospital (Colored)	Charlotte, N. C.
Presbyterian Hospital	Charlotte, N. C.
Wesley Long Hospital (White Only)	Greensboro, N. C.
St. Leo's Hospital	Greensboro, N. C.
L. Richardson Memorial (Colored Only)	Greensboro, N. C.
H. F. Long Hospital, Inc.	Statesville, N. C.
City Memorial Hospital	Winston-Salem, N. C.
Kate Bitting Reynolds Memorial Hospital (Colored)	Winston-Salem, N. C.
Martin Hospital	Mt. Airy, N. C.

WATCH INSPECTORS

A. M. Diggs	Charlotte, N. C.
Neese's Jewelry Company	Greensboro, N. C.
Eugene Fink	Mooresville, N. C.
Iyerly and Steele	Winston-Salem, N. C.
Carl W. Steele	N. Wilkesboro, N. C.
C. E. Kneeburg	Spencer, N. C.
L. T. Holshouser	Salisbury, N. C.